Philips
Component A/V cable

6 ft

Stereo Audio

SWV3312W

Turn up your viewing experience

Step up to a better audio/video connection between components.

Enjoy better picture quality
- 24 carat gold-plated connectors optimize signal

Enjoy better audio quality
- High purity copper conductor for reliable signal transfer

Protects against signal loss
- Copper braided reinforced aluminum shielding

Easy installation
- Color coded connectors for instant recognition
- Plug and play for easy use

Enjoy extended durability
- Flexible PVC jacket
- Protective metal shell for extended durability
- Rubber strain relief

PHILIPS

sense and simplicity

Component A/V cable
6 ft Stereo Audio

SWV3312W/17

Specifications

Outer Carton
- Gross weight: 0.907 kg
- GTIN: 1 06 09585 15138 0
- Outer carton (L x W x H): 27.9 x 20.3 x 12.7 cm
- Nett weight: 0.544 kg
- Number of consumer packagings: 4
- Tare weight: 0.363 kg

Packaging dimensions
- Packaging dimensions (W x H x D): 19.7 x 26.7 x 4.8 cm
- Gross weight: 0.227 kg
- Nett weight: 0.136 kg
- Number of products included: 1
- Packaging type: Blister
- Tare weight: 0.091 kg
- UPC: 6 09585 15138 3

Product highlights

24 carat gold-plated connector
24 carat gold-plated connectors ensure the best signal quality for your components.

High purity copper
This copper conductor provides high accuracy in signal transfer with minimal resistance.

Braided shielding
Copper braided reinforced aluminum shielding protects against signal loss and interference.

Plug and play
Plug and play offers easy installation of components without time-consuming installations.

Color-coded connectors
Color coded connections make it easy to install your cable into the correct inputs and outputs

Metal shell
The metal shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

Flexible PVC Jacket
Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief
Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Issue date 2008-12-05

Version: 1.1.4

12 NC: 8670 000 37952
UPC: 6 09585 15138 3

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com